

BULLARD BOLLARDS

FRATTO Q

Body:

Extruded aluminum body, methacrylate opal diffuser and aluminum upper end cap secured with 4 stainless steel screws.

Light Sources:

Fluorescent Lamps 11W TC-SE, 8W and 24W T5 and 13W TC-DE.

Emissions:

Diffused emission, thanks to the opal finish of the screens.

Power Supply:

Integrated electronic control gear.

Components:

Anchoring plate and spike for ground installation.



Corten
Finishing
.79



Grey
.68




Anthracte
Grey
.86



g@gordonbullard.com
www.bullardbollards.com
269-569-6700



991 South Gull Lake Dr
Richland, MI 49083
USA



BULLARD BOLLARDS

FRATTO Q

FRATTO Q - 500/800

Light Source	Lamps	Wattage	mm [H]
CFL	TC-5C	11	500
CFL	TC-5C	11	800

CODES

mm [H]	
500	76836. _ _
800	76860. _ _



FRATTO Q - 528/800

Light Source	Lamps	Wattage	mm [H]
FL	T5	24	800
FT	T5	8	528

CODES

mm [H]	
800	76837. _ _
528	76835. _ _

g@gordonbullard.com
www.bullardbollards.com
269-569-6700



991 South Gull Lake Dr
Richland, MI 49083
USA

FRATTO Q - 275

Light Source	Lamps	Wattage	mm [H]
CFL	TC-DE	13	275

CODES

mm [H]	
275	76834. _ _

