

BULLARD BOLLARDS

MOON

Body:

Extruded aluminum structure with dissipation cap made of die-cast aluminum alloy. 500, 600 and 700 mm height.

Light Sources:

10W LED Array

Emissions:

Downwards, Single and Twin

Power Supply:

Power factor corrected incorporated electronic ballast.

Components:

Ground prong kit, anchoring spike kit

Accessories:

Spike for ground installation, bracket with anchor bolts

Corten
Finishing
.11



Grey
.68



Satin-Finish
White
.79




g@gordonbullard.com
www.bullardbollards.com
269-569-6700



991 South Gull Lake Dr
Richland, MI 49083
USA





BULLARD BOLLARDS

MOON

Moon - MONOEMISSION

Light Source	Wattage	kg	mm [H]
LED	9W	2.6	500
LED	9W	3.4	700
220-230V / 50-60 HZ			
WW [Warm White]: CRI > 80 / lm 1125 / 3000K			

CODES

kg	mm [H]	
2.6	500	76825.__. WW
3.4	700	76864.__. WW



Moon - BI-EMISSION

Light Source	Wattage	kg	mm [H]
LED	12W	3.1	500
LED	12W	3.5	700
220-230V / 50-60 HZ			
WW [Warm White]: CRI > 80 / lm 840 / 3000K			

CODES

kg	mm [H]	
3.1	500	76826.__. WW
3.5	700	76866.__. WW



g@gordonbullard.com
www.bullardbollards.com
269-569-6700



991 South Gull Lake Dr
Richland, MI 49083
USA